

DRL SINGLE AXLE

SINGLE AXLES FARMING OR GRAPES CARRIAGE TRAILER
WITH BILATERAL HYDRAULIC TITLTING SYSTEM. UP TO
6.000 KG CAPACITY.



STANDARD EQUIPMENTS

- BILATERAL TILTING TANK BY DOUBLE EFFECT RAM AND QUICK CONNECTION WITH TRACTOR OIL
- STAINLESS STEEL AISI 304 FLOWER EMBOSSED TANK FOR FOOD CONVEYING WITH BRUSHED STAINLESS STEEL AND TIG WELDED SHELL
- FLOW DIVIDER HYDRAULIC ENGINE
- FRUITS FLOW CONTROL PANEL
- THE LOWER CENTRE OF GRAVITY ALLOWS THE VEHICLE BOTH TO STAY FIRMLY ON THE ROAD AND DURING UNLOADING
- FOOT STAND SET UP
- HIGH RESISTANCE REINFORCED STRUCTURE
- LEAF SPRING SUSPENSIONS WITH "ADR" 8 COLUMNS INCREASED AXLES (DRL 140-200)
- HYDRAULIC OR AIR BRAKE WITH AUTOMATIC SHUT OFF PARKING BRAKE
- BRAKE CORRECTING DEVICE (ONLY FOR AIR BRAKING SYSTEM)
- INDUSTRIAL TWHEEL WITH 8 HOLES INDUSTRIAL RIM
- POLYURETHANE PAINT WITH EPOXY PRIMER. HIGH WEAR RESISTANCE
- PARACHUTE END-STROKE VALVE
- HYDRAULIC FOOT STAND (SOLO PER DRL 100-120-140-200)
- QUICK CONNECTIONS SUPPORT AND 7-POLE SOCKET
- REAR ZINC-COATED METAL SHEET BUMPERS AND RUBBER BUMPERS
- REMOVABLE ZINC-COATED IRON FENDERS WITH RUBBER BUMPERS AND REAR SPLASH-PROOF
- LIGHTING SYSTEM WITH INDUSTRIAL LIGHTS
- VEHICLES REGISTRATION CERTIFICATES

TECHNICAL INFORMATION

| MOD. | DRL 25 | DRL 50 | DRL 60 |
|---------------------------------|---------------------------|----------------------------|----------------------------|
| Dimensions (cm) | 150x250 - H sideboard: 90 | 220x350 - H sideboard: 100 | 220x400 - H sideboard: 100 |
| Total capacity rate (kg) | 2500 | 5000 | 6000 |
| Unladen Weight (kg) | 700 | 1080 | 1300 |
| Tank capacity (m ³) | 2,5 | 5 | 6,2 |
| Pneumatic | 10,0/80 - R12 PR8 | 13.0/55 - 16 PR16 | 435/50 R19,5 |

OPTIONAL



ZINC-COATED TOOLBOX



STAINLESS STEEL TOOLBOX



SIDE STABILIZER STAND FOOT



HYDRAULIC STAND FOOT



SEMAUTOMATIC COVERAGE WITH TARPULIN



TARPULIN HOSE AND HOOK



WATER JERRY CAN



REAR FENDER WITH STAINLESS STEEL LIGHTS

