

DRL THREE AXLES

THREE AXLES FARMING OR GRAPES CARRIAGE TRAILER WITH BILATERAL HYDRAULIC TITLTING SYSTEM. UP TO 20.000 KG CAPACITY.



STANDARD EQUIPMENTS

- BILATERAL TILTING TANK BY DOUBLE EFFECT RAM AND QUICK CONNECTION WITH TRACTOR OIL
- STAINLESS STEEL AISI 304 FLOWER EMBOSSED TANK FOR FOOD CONVEYING WITH BRUSHED STAINLESS STEEL AND TIG WELDED SHELL
- FLOW DIVIDER HYDRAULIC ENGINE
- FRUITS FLOW CONTROL PANEL
- THE LOWER CENTRE OF GRAVITY ALLOWS THE VEHICLE BOTH TO STAY FIRMLY ON THE ROAD AND DURING UNLOADING
- FOOT STAND SET UP
- HIGH RESISTANCE REINFORCED STRUCTURE
- LEAF SPRING SUSPENSIONS WITH "ADR" 8 COLUMNS INCREASED AXLES (DRL 140-200)
- HYDRAULIC OR AIR BRAKE WITH AUTOMATIC SHUT OFF PARKING BRAKE
- BRAKE CORRECTING DEVICE (ONLY FOR AIR BREAKING SYSTEM)
- INDUSTRIAL TWHEEL WITH 8 HOLES INDUSTRIAL RIM
- POLYURETHANE PAINT WITH EPOXY PRIMER. HIGH WEAR RESISTANCE
- PARACHUTE END-STROKE VALVE
- HYDRAULIC FOOT STAND (SOLO PER DRL 100-120-140- 200)
- QUICK CONNECTIONS SUPPORT AND 7-POLE SOCKET
- REAR ZINC-COATED METAL SHEET BUMPERS AND RUBBER BUMPERS
- REMOVABLE ZINC-COATED IRON FENDERS WITH RUBBER BUMPERS AND REAR SPLASH-PROOF
- LIGHTING SYSTEM WITH INDUSTRIAL LIGHTS
- VEHICLES REGISTRATION CERTIFICATES

TECHNICAL INFORMATION

MOD.	DRL 200
Dimensions (cm)	240x585 - H sideboard: 165
Axles No.	3
Total capacity rate (kg)	20000
Unladen Weight (kg)	58000
Tank capacity (m³)	18,5
Pneumatic	385/55 R22.5
Braking	PNEUMATICS

OPTIONAL



ZINC-COATED
TOOLBOX



STAINLESS STEEL
TOOLBOX



SIDE STABILIZER
STAND FOOT



WATER JERRY
CAN



STAINLESS
INSPECTION
STEPLADDER



TARPAULIN HOSE
AND HOOK



REAR FENDER
WITH STAINLESS
STEEL LIGHTS



SEMI-AUTOMATIC
COVERAGE WITH
TARPAULIN